



1001 Trout Brook Crossing
Rocky Hill, CT 06067-3910
Telephone: (860) 571-5100
FAX: (860) 571-5465

Product Description Sheet

Diaphragm Dispense Valve

Part # 97135

North American Equipment, November 2003

PRODUCT DESCRIPTION

The LOCTITE® Diaphragm Valve is a pneumatically activated dispense valve that utilizes a floating PTFE diaphragm. The valve can be stationary mounted or hand held in conjunction with pressure-time dispense systems. The opening of the diaphragm takes place by pressurizing the internal single acting cylinder. Closure is achieved by spring force between cycles. It is suitable for use with acrylic and anaerobic adhesives up to 2500cP, but not suited for cyanoacrylate products

PRODUCT FEATURES

- Cost effective valve for use with pressure-time systems.
- Modular design and floating diaphragm allow for easy cleaning or repair.
- Fail safe spring assisted close.
- Internal components are PTFE to prevent premature curing.
- Flow rates can be increased with use of 3/8" feedline.



Technical Data

- Pneumatic supply min. 5 bar (73 psi); max. 7 bar (100 psi)
- Air supply required: Filtered 10 µm, oil-free, non-condensing.
- Pneumatic control hose size dia: 4 mm
- Product feedline is standard: 1/4 inch.
- Optional: feedline upgrade kit to 3/8 inch (item #97220)
- Dispensing pressure range of the valve: 0.5 bar (7 psi) to 4 bar (60 psi).
- Weight 300 g.
- Dimensions: overall length: 127 mm. diameter: 32 mm.
- Internal product bore of ø 2 mm.

Recommended Spare Parts

Description	Part Number
• Actuator assembly	97254
• Shut off valve	97268
• Luer-Lok adapter kit	97233
• Feedline 1/4" PTFE lined	97972
• Feedline upgrade kit 1/4" to 3/8"	97220

If required air quality is not achieved, install a Loctite® filter regulator. Accessory Order No. 985397.

NOT FOR PRODUCT SPECIFICATIONS

PLEASE CONTACT LOCTITE CORPORATION FOR ASSISTANCE: 1-800-LOCTITE (1-800-562-8483)

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, LOCTITE CORPORATION SPECIFICALLY DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARISING FROM SALE OR USE OF LOCTITE CORPORATION'S PRODUCTS. LOCTITE CORPORATION SPECIFICALLY DISCLAIMS ANY LIABILITY FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OF ANY KIND, INCLUDING LOST PROFITS. The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Loctite Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Loctite is a trademarks of Loctite Corp. U.S.A.